
déanta

Technical Data Sheet

FRNM6GPG EI30

EI30

PRIMED DOOR





Timber Fire Door Manufacture

0012

QUALITY CONTROL CHECKS

Type; Design	Fire Rated EI30
Construction	Glased (Clear) PBC
Durability	Pass
Finish	Primed RAL 9007 White (Water based) Matt

SPECIFICATIONS

Product Type	Internal door – Glased (Clear)
Intended use	Internal fire door
Lipping (stiles)	25mm Poplar
Lipping (rails)	25mm Poplar
Inner Lipping	N/A
Stiles/Rails/Core	Chipboard + MDF
Beadings	15x15.5mm MDF removable beading
Panels	N/A
Door Finish	Primed RAL 9007 White (Water based) Matt
Door Weights	32-33 KG
Glass	PyroGuard Ew30 Impact, 7mm Fire Glass (CF257) With SealmasterIntumescent (CF5645)

SIZES AVAILABLE

2032 x 864 x 44mm
2032 x 813 x 44mm

GLAZED OPTIONS

CL
Clear

FIRE TESTING

Successfully fire tested in accordance with the requirements of **EN 1634-1**.
Certification Number: **WF399992 Rev E**
Efectis Extended Application Report: **EFR-23-005536-EXAP**

Head Office: Dingle Road, Curraheen, Tralee, Co. Kerry, V92 EH6E.
Dublin Warehouse: 2 Cloverhill Industrial Estate, Dublin 22, D22 VP70.
P: (066) 71 94828 | W: www.deantadoors.ie | E: sales@deantadoors.ie